

View Online at <https://aerobasegroup.com/nsn/5910-01-466-7964>

**Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 2.000 inches and 2.250 inches

**Body Diameter:**

0.312 inches

**Body Length:**

Between 0.625 inches and 0.672 inches

**Terminal Diameter:**

Between 0.025 inches and 0.027 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Impedance At Minimum Operating Temperature In Ohms:**

15.0

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

470.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

125.0 microamperes

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Capacitive Electrode Material:**

Tantalum

**Power Factor At Reference Temperature In Percent:**

0.600

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.85

**Dc Leakage At Reference Temp:**

2.000 microamperes

**Reference Temperature At Which Rated:**

85.0 degrees celsius

**Terminal Type And Quantity:**

2 insulated wire lead

**Specification Data:**

14933-93026 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0