

View Online at <https://aerobasegroup.com/nsn/5910-01-466-8322>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.100

Terminal Length:

Between 31.8 millimeters and 44.5 millimeters

Body Diameter:

Between 3.7 millimeters and 4.3 millimeters

Body Length:

Between 13.8 millimeters and 15.4 millimeters

Terminal Diameter:

Between 0.5 millimeters and 0.6 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

Electrical Polarization:

Nonpolarized

Section Quantity:

2

Capacitance Value Per Section:

0.110 microfarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc all sections

Tolerance Range Per Section:

-10.00/+10.00 percent all sections

Capacitive Electrode Material:

Tantalum

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-39003/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0