## NSN 5910-01-467-5461

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-467-5461 **Body Style:** W/thd bushing mtg, terminals on opposite ends **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.010 **Terminal Length:** 1.625 inches **Body Diameter:** 0.562 inches **Body Length:** 1.375 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Mounting Facility Screw Thread Series Designator:** Unf **Mounting Facility Type And Quantity:** 1 threaded mounting studs **Features Provided:** Mounting hardware **Capacitance Value Per Section:** 0.270 microfarads single section **Nonderated Operating Temp:** Between 65.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.312 inches Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Thread Tolerance Class:** 2a external **Case Material:** Metal **Case Insulation Material:** Paper or plastic or rubber **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5910-01-467-5461

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0