

View Online at <https://aerobasegroup.com/nsn/5910-01-467-8139>

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

1.000

Terminal Length:

31.8 millimeters

Body Length:

Between 4.6 millimeters and 5.1 millimeters

Body Width:

Between 4.6 millimeters and 5.1 millimeters

Body Height:

Between 2.1 millimeters and 2.5 millimeters

Center To Center Distance Between Terminals Parallel To Length:

Between 4.7 millimeters and 5.5 millimeters

Terminal Diameter:

Between 0.6 millimeters and 0.7 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

30.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-20/35 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0