NSN 5910-01-467-8143

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-467-8143

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.010

Body Length:

Between 7.1 millimeters and 7.6 millimeters

Body Width:

Between 7.1 millimeters and 7.6 millimeters

Body Height:

Between 2.1 millimeters and 2.5 millimeters

Center To Center Distance Between Terminals Parallel To Length:

Between 4.4 millimeters and 4.9 millimeters

Terminal Diameter:

Between 0.6 millimeters and 0.7 millimeters

Terminal Height From Body:

31.8 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

1000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Tolerance Range Per Section:

-1.00/+1.00 percent single section

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-20/36 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5910-01-467-8143

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0