

View Online at <https://aerobasegroup.com/nsn/5910-01-467-8143>

**Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.010

**Body Length:**

Between 7.1 millimeters and 7.6 millimeters

**Body Width:**

Between 7.1 millimeters and 7.6 millimeters

**Body Height:**

Between 2.1 millimeters and 2.5 millimeters

**Center To Center Distance Between Terminals Parallel To Length:**

Between 4.4 millimeters and 4.9 millimeters

**Terminal Diameter:**

Between 0.6 millimeters and 0.7 millimeters

**Terminal Height From Body:**

31.8 millimeters

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Capacitance Value Per Section:**

1000.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:**

0.0 single section

**Nonderated Continuous Voltage Rating And Type Per Section:**

200.0 dc single section

**Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:**

-30.0/+30.0 single section

**Tolerance Range Per Section:**

-1.00/+1.00 percent single section

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Specification Data:**

81349-mil-c-20/36 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0