## NSN 5910-01-468-6632

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-468-6632 **Body Style:** Chip type **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.100 **Terminal Length:** 0.030 inches **Body Length:** Between 0.185 inches and 0.215 inches **Body Width:** Between 0.085 inches and 0.115 inches **Body Height:** Between 0.035 inches and 0.065 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 2.200 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 microfarads single section **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 6.000 **Equivalent Series Resistance At Reference Tempurature In Ohms:** Dc Leakage At Reference Temp: 1.000 microamperes **Terminal Type And Quantity:** 2 bonding pad Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5910-01-468-6632

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0