

View Online at https://aerobasegroup.com/nsn/5910-01-470-0504

view Online at https://aerobasegroup.com/hsh/5910-01-470-0504
Body Style:
Chip type
Reliability Indicator:
Not established
Body Length:
2.2 millimeters
Body Width:
1.45 millimeters
Body Height:
1.3 millimeters
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
6625-01-451-8727
Capacitance Value Per Section:
4700.000 picofarads single section
Nonderated Operating Temp:
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No