NSN 5910-01-474-5465

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-474-5465
Body Style:
Chip type
Reliability Indicator:
Not established
Body Length:
0.078 inches
Body Width:
0.049 inches
Body Height:
0.055 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
1430-01-433-8025
Capacitance Value Per Section:
470.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Surface Treatment:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Surface Treatment: Nickel and silver
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Surface Treatment: Nickel and silver Terminal Type And Quantity:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Surface Treatment: Nickel and silver Terminal Type And Quantity: 2 bonding pad
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Surface Treatment: Nickel and silver Terminal Type And Quantity: 2 bonding pad Shelf Life:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Surface Treatment: Nickel and silver Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Surface Treatment: Nickel and silver Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Surface Treatment: Nickel and silver Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Surface Treatment: Nickel and silver Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: