NSN 5910-01-475-2962

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-475-2962

view Online at https://aerobasegroup.com/hsh/5910-01-475-2962
Body Style:
Dual inline
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.000
Terminal Length:
0.140 inches
Body Length:
0.260 inches
Body Width:
0.092 inches
Body Height:
0.155 inches
Center To Center Distance Between Terminals Parallel To Length:
0.325 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
10000.0 megohms
Capacitance Value Per Section:
1000.000 picofarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
-25.0/+15.0 without voltage applied single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohms
Test Data Document:
81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 printed circuit
Specification Data:
81349-mil-c-39014/22 government specification

N/a

Shelf Life:

NSN 5910-01-475-2962

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0