

View Online at https://aerobasegroup.com/nsn/5910-01-475-9614

Body Style:Chip typeReliability Indicator:EstabilishedReliability Failure Rate Level In Percent:0.010Body Length:0.080 inchesBody Width:0.050 inchesBody Height:Between 0.022 inches and 0.055 inchesSchematic Diagram Designator:No common or grounded electrode (s)Capacitance Value Per Section:300.000 picofarads single sectionBetween -55.0 degrees celsius and 125.0 degrees celsiusHonderated Continuous Voltage Rating And Type Per Section:100.0 dc single section100.0 dc single section100.0 dc single section2 bonding padSheff Life:N/aUnit Of Measure:"NaFing:Fing:	
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.080 inches Body Width: 0.050 inches Body Height: 0.050 inches Body Height: Between 0.022 inches and 0.055 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 3300.000 picofarads single section Monderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius 100.0 dc single section 100.0 dc single section 100.0 dc single section 10.00/+10.00 percent single section 10.00/+10.00 percent single section Ya National Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Style:
Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.080 inches Body Width: 0.050 inches Body Height: 0.050 inches Body Height: 0.050 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 3300.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Ciolon de	Chip type
Reliability Failure Rate Level In Percent:0.010Body Length:0.080 inchesBody Width:0.050 inchesBody Height:Between 0.022 inches and 0.055 inchesSchematic Diagram Designator:No common or grounded electrode (s)Capacitance Value Per Section:3300.000 picofarads single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 125.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:100.0 dc single sectionTolerance Range Per Section:-10.00/+10.00 percent single sectionTerminal Type And Quantity:2 bonding padShelf Life:N/aUnit Of Measure:Demilitarization:No	Reliability Indicator:
0.010 Body Length: 0.080 inches Body Width: 0.050 inches Body Height: Botween 0.022 inches and 0.055 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 3300.000 picofarads single section Monderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: 10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Established
Body Length: 0.080 inches Body Width: 0.050 inches Body Height: Between 0.022 inches and 0.055 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 3300.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Reliability Failure Rate Level In Percent:
0.080 inches Body Width: 0.050 inches Body Height: Between 0.022 inches and 0.055 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 3300.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.010
Body Width: 0.050 inches Body Height: Between 0.022 inches and 0.055 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 3300.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Length:
0.050 inches Body Height: Between 0.022 inches and 0.055 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 3300.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.080 inches
Body Height: Between 0.022 inches and 0.055 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 3300.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Width:
Between 0.022 inches and 0.055 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 3300.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section 100.0 dc single section 100.0 dc single section 100.0 dc single section 100.0 dc single section 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.050 inches
Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 3300.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Height:
No common or grounded electrode (s) Capacitance Value Per Section: 3300.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.022 inches and 0.055 inches
Capacitance Value Per Section: 3300.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Schematic Diagram Designator:
3300.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	No common or grounded electrode (s)
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Capacitance Value Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	3300.000 picofarads single section
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Nonderated Operating Temp:
100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between -55.0 degrees celsius and 125.0 degrees celsius
Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Nonderated Continuous Voltage Rating And Type Per Section:
-10.00/+10.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	100.0 dc single section
Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Tolerance Range Per Section:
2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	-10.00/+10.00 percent single section
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No	2 bonding pad
Unit Of Measure: Demilitarization: No	Shelf Life:
 Demilitarization: No	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Fiig:	No
	Fiig:
A010b0	A010b0