

View Online at <https://aerobasegroup.com/nsn/5910-01-476-7749>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.002

Terminal Length:

Between 35.0 millimeters and 45.0 millimeters

Body Diameter:

10.0 millimeters

Body Length:

26.5 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Ari 5972 doppler 72

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

1.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 100.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc single section

Tolerance Range Per Section:

-5.00/+5.00 microfarads single section

Case Material:

Plastic

Dielectric Material:

Plastic polyester

Case Insulation Material:

Plastic

Special Features:

160 vac; used for blocking, bypassing, filtering, timing, coupling and decoupling, interference suppression in low voltage application; aluminum electrodes

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0