NSN 5910-01-478-1732

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-478-1732

3
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.000
Terminal Length:
1.250 inches
Body Length:
0.190 inches
Body Width:
0.190 inches
Body Height:
0.090 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.185 inches and 0.215 inches
Terminal Diameter:
Between 0.023 inches and 0.029 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
Circuit card assembly/fighter aircraft f-18 e/f
Insulation Resistance At Maximum Operating Temp:
100000.000 megohms
Capacitance Value Per Section:
100000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Criticality Code Justification:
Agav
Talananaa Banna Ban Caatiana

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Insulation Resistance At Reference Temp:

100000.0 megohms

Special Features:

Configuration with standoff

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-prf-39014/1h government specification

NSN 5910-01-478-1732

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



N/a		
Unit Of Measure:		
Demilitarization:		
No		
Fiig:		
A010b0		

Mil-std (military Standard):

Shelf Life:

Mil-prf-39014 spec.