## NSN 5910-01-478-8128

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-478-8128
Body Style:
Chip type
Reliability Indicator:
Not established
Body Length:
0.220 inches
Body Width:
0.250 inches
Body Height:
Between 0.020 inches and 0.065 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
Kg-207
Capacitance Value Per Section:
4700.000 picofarads single section
Nonderated Operating Temp:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -10.00/+10.00 picofarads single section
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -10.00/+10.00 picofarads single section  Terminal Surface Treatment:
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:  -10.00/+10.00 picofarads single section  Terminal Surface Treatment:  Solder
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 picofarads single section  Terminal Surface Treatment: Solder  Terminal Type And Quantity:
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 picofarads single section  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 bonding pad
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 picofarads single section  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 bonding pad  Shelf Life:
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 picofarads single section  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 picofarads single section  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 picofarads single section  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure:
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 picofarads single section  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure: Demilitarization: