

View Online at https://aerobasegroup.com/nsn/5910-01-479-3564

Body Style:	
Chip type	
Reliability Indicator:	
Established	
Reliability Failure Rate Lev	el In Percent:
0.0100	
Body Length:	
0.180 inches	
Body Width:	
0.050 inches	
Body Height:	
Between 0.022 inches and 0	.055 inches
Schematic Diagram Desigr	nator:
No common or grounded ele	ctrode (s)
End Application:	
Electronic component	
Capacitance Value Per Sec	tion:
12000.000 picofarads single	section
Nonderated Operating Terr	າ p :
Between -55.0 degrees celsi	us and 125.0 degrees celsius
Nonderated Continuous Vo	bltage Rating And Type Per Section:
50.0 dc single section	
Tolerance Of Tempurature	Coefficient Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section	
Criticality Code Justification	on:
Agav	
Tolerance Range Per Secti	on:
-10.00/+10.00 percent single	section
Case Material:	
Ceramic or glass	
Special Features:	
Termination finish is base me	etallization-barrier metal-solder (min thick of 60 micro-inches) tin/lead alloy
Test Data Document:	
81349-mil-c-55681 specificat	tion (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercia	al catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performa	nce requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantit	y:
2 bonding pad	
Shelf Life:	
N/a	
Unit Of Measure:	

- Demilitarization:
- No

NSN 5910-01-479-3564 Ceramic Dielectric Fixed Capacitor - Page 2 of 2

Fiig: A010b0

