NSN 5910-01-480-8903

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-480-8903 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 2.250 inches **Body Diameter:** 0.406 inches **Body Length:** Between 1.046 inches and 1.093 inches **Terminal Diameter:** Between 0.025 inches and 0.027 inches **Impedance At Minimum Operating Tempurature In Ohms:** 5.0 **Capacitance Value Per Section:** 4700.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 35.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 6.0 ac/dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: Equivalent Series Resistance At Reference Tempurature In Ohms:** 0.30 Dc Leakage At Reference Temp: 10.000 microamperes **Special Features:** Insulating sleeve laps over ends of case; leads are tinned nickel, solderable, and weldable; no continuous reverse voltage permissable **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5910-01-480-8903

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0