

View Online at <https://aerobasegroup.com/nsn/5910-01-482-0813>

**Body Style:**

Chip type

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.0100

**Terminal Length:**

0.030 inches

**Body Length:**

0.180 inches

**Body Width:**

0.080 inches

**Body Height:**

Between 0.022 inches and 0.080 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

5998-01-482-0976

**Capacitance Value Per Section:**

56000.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:**

0.0 single section

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:**

-15.0/+15.0 single section

**Criticality Code Justification:**

Agav

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Ceramic or glass

**Dissipation Factor At Reference Temperature In Percent:**

0.0500

**Special Features:**

Termination finish is base metallization-barrier metal-solder coated min thick of 60 micro-inches (tin/lead alloy)

**Test Data Document:**

81349-mil-c-55681 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 bonding pad

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0