

View Online at <https://aerobasegroup.com/nsn/5910-01-482-0914>

Body Style:

Chip type

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.0100

Terminal Length:

0.5 millimeters

Body Length:

2.0 millimeters

Body Width:

1.2 millimeters

Body Height:

1.3 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Controller assembly, circuit card assembly

Capacitance Value Per Section:

43.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Criticality Code Justification:

Agav

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Ceramic or ceramic or glass

Dissipation Factor At Reference Temperature In Percent:

0.0500

Special Features:

Termination finish is base metallization-barriermetal-solder coated min thick of 60 micro-inches (tin/lead alloy)

Test Data Document:

81349-mil-c-55681 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 bonding pad

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0