

View Online at <https://aerobasegroup.com/nsn/5910-01-484-2107>

**Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.010

**Terminal Length:**

Between 1.250 inches and 1.750 inches

**Body Diameter:**

Between 0.110 inches and 0.141 inches

**Body Length:**

Between 0.219 inches and 0.281 inches

**Terminal Diameter:**

0.025 inches

**Terminal Height From Body:**

0.094 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

120.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

10.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 microfarads single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

4.000

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.90

**Dc Leakage At Reference Temp:**

0.400 microamperes

**Special Features:**

Sleeved

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0