## NSN 5910-01-487-1385

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/ns	n/5910-01-487-1385
Body Style:	
W/mtg bracket, axial terminals	
Reliability Indicator:	
Established	
Reliability Failure Rate Level In Percent:	
0.100	
Terminal Length:	
Between 1.625 inches and 2.625 inches	
Body Diameter:	
Between 0.969 inches and 1.030 inches	
Body Length:	
Between 2.313 inches and 2.437 inches	
Terminal Diameter:	
Between 0.235 inches and 0.312 inches	
Unthreaded Mounting Hole Diameter:	
Between 0.151 inches and 0.161 inches	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
Mounting Facility Type And Quantity:	
1 unthreaded mounting holes	
Features Provided:	
Hermetically sealed case and mounting hards	vare
Capacitance Value Per Section:	
10.000 picofarads single section	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 125.0 deg	grees celsius
Nonderated Continuous Voltage Rating Ar	d Type Per Section:
200.0 dc single section	
Tolerance Range Per Section:	
-20.00/+20.00 percent single section	
Case Material:	
Metal	
Dielectric Material:	
Paper and plastic	
Terminal Type And Quantity:	
2 uninsulated wire lead	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
B 111. 1 .1	

No

Demilitarization:

## NSN 5910-01-487-1385

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0