NSN 5910-01-487-1935

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5910-01-487-1935 |
|---|
| Body Style: |
| Chip type |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.100 |
| Terminal Length: |
| 0.020 inches |
| Body Length: |
| 0.080 inches |
| Body Width: |
| 0.050 inches |
| Body Height: |
| 0.055 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| End Application: |
| 5865-01-346-4772 |
| Capacitance Value Per Section: |
| 6.800 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Terminal Type And Quantity: |
| 2 bonding pad |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A010b0 |
| Mil-std (military Standard): |

Mil-prf-55681 spec.