NSN 5910-01-488-7766

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-488-7766 **Body Style:** Chip type **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.001 **Body Length:** 5.08 millimeters **Body Width:** 1.27 millimeters **Body Height:** 1.27 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Electrical Polarization:** Nonpolarized **Section Quantity:** 1 **Capacitance Value Per Section:** 0.680 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** Dc Leakage At Reference Temp: 1.000 microamperes **Terminal Surface Treatment:** Gold **Precious Material And Location:** Terminals gold **Terminal Type And Quantity:** 2 bonding pad Shelf Life:

N/a

NSN 5910-01-488-7766

Electrolytic Fixed Capacitor - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A010b0