NSN 5910-01-493-3026

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-493-3026 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.010 **Terminal Length:** Between 2.000 inches and 2.500 inches **Body Diameter:** 0.312 inches **Body Length:** Between 0.625 inches and 0.672 inches **Terminal Diameter:** Between 0.023 inches and 0.027 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Electrical Polarization:** Polarized **Section Quantity: Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 82.000 microfarads single section **Nonderated Operating Temp:** 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 microfarads single section Case Material: Metal **Capacitive Electrode Material: Tantalum** Dc Leakage At Reference Temp: 4.000 microamperes **Terminal Type And Quantity:** 2 wire braid Shelf Life:

Unit Of Measure:

N/a

NSN 5910-01-493-3026

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0