## NSN 5910-01-497-0115

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-497-0115
Body Style:
Chip type
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.000
Body Length:
3.20 millimeters
Body Width:
2.50 millimeters
Body Height:
1.50 millimeters
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
2350-01-455-3174
Capacitance Value Per Section:
100000.000 picofarads single section
100000.000 picofarads single section  Nonderated Operating Temp:
Nonderated Operating Temp:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section:
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Terminal Type And Quantity: 2 bonding pad
Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Terminal Type And Quantity: 2 bonding pad  Shelf Life:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Terminal Type And Quantity: 2 bonding pad  Shelf Life:  N/a
Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Terminal Type And Quantity: 2 bonding pad  Shelf Life:  N/a
Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Terminal Type And Quantity: 2 bonding pad  Shelf Life: N/a  Unit Of Measure:  Demilitarization: