NSN 5910-01-498-3032

Electrolytic Fixed Capacitor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5910-01-498-3032 |
|---|
| Body Style: |
| Chip type |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.010 |
| Body Length: |
| 0.200 inches |
| Body Width: |
| 0.100 inches |
| Body Height: |
| 0.050 inches |
| Schematic Diagram Designator: |
| Electrod (s) grounded to case, w/gnd terminal |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 6.800 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 10.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Capacitive Electrode Material: |
| Tantalum |
| Terminal Type And Quantity: |
| 2 bonding pad |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A010b0 |