NSN 5910-01-506-5710

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-506-5710 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.100 **Terminal Length:** 38.1 millimeters **Body Diameter:** 7.34 millimeters **Body Length:** 15.03 millimeters **Terminal Diameter:** 0.64 millimeters **Terminal Height From Body:** 5.85 millimeters **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Electrical Polarization:** Nonpolarized **Section Quantity:** 1 **Capacitance Value Per Section:** 270.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 microfarads single section Case Material: Metal **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** Dc Leakage At Reference Temp: 15.000 microamperes **Case Insulation Material:**

Terminal Type And Quantity:

2 wire braid

Plastic

NSN 5910-01-506-5710

Electrolytic Fixed Capacitor - Page 2 of 2



Shelf	LIIE.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0