

View Online at <https://aerobasegroup.com/nsn/5910-01-509-1256>

**Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:**

Established

**Terminal Length:**

Between 2.000 inches and 2.500 inches

**Body Diameter:**

Between 0.275 inches and 0.297 inches

**Body Length:**

Between 0.625 inches and 0.672 inches

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

82.000 microfarads single section

**Nonderated Operating Temp:**

Between 55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

75.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 picofarads single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

2.000

**Test Data Document:**

81349-mil-c-39006 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Specification Data:**

81349-mil-c-39006/25 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0