NSN 5910-01-512-8196

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-512-8196 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 1.500 inches **Body Diameter:** Between 0.119 inches and 0.151 inches **Body Length:** Between 0.255 inches and 0.317 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Solid **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 240000.000 picofarads single section **Nonderated Operating Temp:** Between -80.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 0.7 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Dissipation Factor At Reference Tempurature In Percent:** 2.0000 Dc Leakage At Reference Temp:

0.600 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic Terminal Type And Quantity:** 2 uninsulated wire lead

NSN 5910-01-512-8196

Electrolytic Fixed Capacitor - Page 2 of 2



| She | lf | I if | ρ. |
|-----|-----|------|----|
| ~ | ••• | | • |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0