NSN 5910-01-513-9866

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-513-9866
Body Style:
Chip type
Reliability Indicator:
Not established
Body Length:
0.063 inches
Body Width:
0.032 inches
Body Height:
0.035 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
27.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Terminal Type And Quantity:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Terminal Type And Quantity: 2 bonding pad
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: