NSN 5910-01-516-6263

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-516-6263						
Body Style:						
Without mounting facilities, terminal (s) on one surface						
Reliability Indicator:						
Not established						
Terminal Length:						
1.250 inches						
Body Length:						
0.250 inches						
Body Width:						
0.200 inches						
Body Height:						
0.220 inches						
Center To Center Distance Between Terminals Parallel To Length:						
Between 0.140 inches and 0.200 inches						
Terminal Diameter:						
Between 0.023 inches and 0.027 inches						
Schematic Diagram Designator:						
Two terminals common to one electrode						
End Application:						
1430-01-418-4396; wsd: missile, patriot						
Insulation Resistance At Maximum Operating Temp:						
1000.0 megohms						
Capacitance Value Per Section:						
165.000 picofarads single section						
Nonderated Operating Temp:						
Between -55.0 degrees celsius and 125.0 degrees celsius						
Nonderated Continuous Voltage Rating And Type Per Section:						
1000.0 dc single section						
Tolerance Range Per Section:						
+0.00/+30.00 picofarads single section						
Insulation Resistance At Reference Temp:						
10000.0 megohms						
Terminal Surface Treatment:						
Solder						
Case Insulation Material:						
Plastic or rubber						
Terminal Type And Quantity:						
2 wire braid						
Specification Data:						
81349-mil-prf-49467b government specification						

N/a

Shelf Life:

NSN 5910-01-516-6263

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A010b0

Mil-std (military Standard):

Mil-prf-49467b spec.