## NSN 5910-01-516-6266

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-516-6266
Body Style:
Without mounting facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length:
0.320 inches
Body Width:
0.200 inches
Body Height:
0.280 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.140 inches and 0.200 inches
Terminal Diameter:
Between 0.023 inches and 0.027 inches
Schematic Diagram Designator:
Two terminals common to one electrode
End Application:
1430-01-418-4396; wsd: missile, patriot
Insulation Resistance At Maximum Operating Temp:
1000.0 megohms
Capacitance Value Per Section:
1650.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
1000.0 dc single section
Tolerance Range Per Section:
+0.00/+300.00 picofarads single section
Insulation Resistance At Reference Temp:
10000.0 megohms
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic or rubber
Terminal Type And Quantity:
2 wire braid
Specification Data:
81349-mil-prf-49467b government specification

N/a

Shelf Life:

## NSN 5910-01-516-6266

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



):

--

Demilitarization:

No

Fiig:

A010b0

Mil-std (military Standard):

Mil-prf-49467b spec.