

View Online at <https://aerobasegroup.com/nsn/5910-01-521-6699>

Body Style:

Chip type

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

8.000

Body Length:

Between 3.3 millimeters and 3.7 millimeters

Body Width:

Between 2.6 millimeters and 3.0 millimeters

Body Height:

Between 1.7 millimeters and 2.1 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

Electrical Polarization:

Polarized

Capacitance Value Per Section:

3.300 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Capacitive Electrode Material:

Tantalum

Product Name:

Capacitors, chip, fixed, tantalum, polarized established reliability and nonestablished reliability, style cwr11 (metric)

Terminal Type And Quantity:

2 bonding pad

Specification Data:

81349-mil-prf-55365/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0

Mil-std (military Standard):

Mil-prf-55365 spec.