

View Online at <https://aerobasegroup.com/nsn/5910-01-521-8390>

**Body Style:**

Chip type

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

8.000

**Body Length:**

Between 5.7 millimeters and 6.3 millimeters

**Body Width:**

Between 2.9 millimeters and 3.5 millimeters

**Body Height:**

Between 2.2 millimeters and 2.8 millimeters

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

4.700 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

20.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Capacitive Electrode Material:**

Tantalum

**Product Name:**

Capacitors, chip, fixed, tantalum, polarized established reliability and nonestablished reliability, style cwr11 (metric)

**Terminal Type And Quantity:**

2 bonding pad

**Specification Data:**

81349-mil-prf-55365/8 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0

**Mil-std (military Standard):**

Mil-prf-55365 spec.