## NSN 5910-01-522-4010

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-522-4010 **Body Style:** Chip type **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.0100 **Terminal Length:** 0.5 millimeters **Body Length:** 3.2 millimeters **Body Width:** 1.6 millimeters **Body Height:** 1.3 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** 5998-01-522-4009 **Capacitance Value Per Section:** 100.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Criticality Code Justification:** Aarh and agav **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material:** Glass or ceramic **Special Features:** Termination finish is base metallization-barrier metal-solder coated with a min of 4 percent lead (tin/lead alloy) **Terminal Type And Quantity:** 2 bonding pad Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5910-01-522-4010

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0