

View Online at https://aerobasegroup.com/nsn/5910-01-522-4767

### Body Style:

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.001

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

Between 0.307 inches and 0.327 inches

Body Length:

Between 0.844 inches and 0.906 inches

**Terminal Diameter:** 

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

#### Insulation Resistance At Maximum Operating Temp:

250.0 megohms

#### Capacitance Value Per Section:

0.033 microfarads single section

#### Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 microfarads single section

#### Case Material:

Metal

# Insulation Resistance At Reference Temp:

25000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.000

# **Terminal Surface Treatment:**

Solder

### Case Insulation Material:

Plastic

#### **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0