

View Online at <https://aerobasegroup.com/nsn/5910-01-523-2574>

Body Style:

Chip type

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.001

Body Length:

0.180 inches

Body Width:

0.050 inches

Body Height:

Between 0.022 inches and 0.055 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Nsn 5821-01-387-0594 receiver-transmitter, radio

Capacitance Value Per Section:

10000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-25.0/+15.0 with rated voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Product Name:

Cpart name assigned by controlling agency; capacitors, chip multiple layer, fixed, ceramic dielectric, established reliability and non-established reliability, styes cdr01, cdr02, cdr03, and cdr04

Test Data Document:

81349-mil-c-55681 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 bonding pad

Specification Data:

81349-mil-c-55681/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0