## NSN 5910-01-527-2320

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-527-2320

Body Style:
W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Body Length:
3.940 inches
Body Width:
2.910 inches
Body Height:
1.940 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
24.000 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 70.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
400.0 ac-peak single section
400.0 ac-peak single section  Tolerance Range Per Section:
•
Tolerance Range Per Section:
Tolerance Range Per Section: -10.00/+10.00 percent single section
Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity:
Tolerance Range Per Section: -10.00/+10.00 percent single section Terminal Type And Quantity: 2 threaded stud
Tolerance Range Per Section: -10.00/+10.00 percent single section  Terminal Type And Quantity: 2 threaded stud  Shelf Life:
Tolerance Range Per Section: -10.00/+10.00 percent single section  Terminal Type And Quantity: 2 threaded stud  Shelf Life: N/a
Tolerance Range Per Section: -10.00/+10.00 percent single section  Terminal Type And Quantity: 2 threaded stud  Shelf Life: N/a
Tolerance Range Per Section: -10.00/+10.00 percent single section  Terminal Type And Quantity: 2 threaded stud  Shelf Life: N/a  Unit Of Measure:
Tolerance Range Per Section: -10.00/+10.00 percent single section  Terminal Type And Quantity: 2 threaded stud  Shelf Life: N/a Unit Of Measure: Demilitarization:
Tolerance Range Per Section: -10.00/+10.00 percent single section  Terminal Type And Quantity: 2 threaded stud  Shelf Life: N/a Unit Of Measure: Demilitarization: No