## NSN 5910-01-530-7534

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-530-7534 **Body Style:** Chip type **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 1.0000 **Body Length:** 0.110 inches **Body Width:** 0.110 inches **Body Height:** 0.102 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 100000.0 megohms **Capacitance Value Per Section:** 62.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 90.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -20.0/+20.0 single section **Tolerance Range Per Section:** -2.00/+2.00 percent single section **Case Material:** Ceramic **Insulation Resistance At Reference Temp:** 1000000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.0500 **Terminal Surface Treatment:** Silver or palladium **Precious Material And Location:** Terminal surfaces palladium or terminal surfaces silver **Terminal Type And Quantity:** 2 bonding pad

N/a

Shelf Life:

## NSN 5910-01-530-7534

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0