

View Online at <https://aerobasegroup.com/nsn/5910-01-531-2107>

Body Style:

Chip type

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.001

Terminal Length:

Between 0.012 inches and 0.021 inches

Body Length:

Between 0.117 inches and 0.133 inches

Body Width:

Between 0.049 inches and 0.070 inches

Body Height:

Between 0.020 inches and 0.051 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Nsn 1440-01-444-4239; launching station, guided missile, semitrailer mounted; w/s: multiple launch rocket system (mlrs)

Section Quantity:

3

Capacitance Value Per Section:

1000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Ceramic

Dissipation Factor At Reference Temperature In Percent:

0.150

Special Features:

Base metalization: barrier metal - tinned (tin or tin/lead alloy); solderguard ii

Precious Material And Location:

Bonding pads over electrodes silver

Terminal Type And Quantity:

2 bonding pad

Specification Data:

81349 - cdr32b+102blws government specification

Specification Or Standard:

81349 mil-prf-55681/8 reference number

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0

Mil-std (military Standard):

Mil-prf-55681 spec.