

View Online at <https://aerobasegroup.com/nsn/5910-01-532-9091>

Body Style:

W/o mtg facilities, radial terminals

Terminal Length:

0.187 inches

Body Diameter:

0.350 inches

Body Length:

0.710 inches

Center To Center Distance Between Terminals Parallel To Length:

0.200 inches

Terminal Diameter:

0.020 inches

Electrical Polarization:

Polarized

End Application:

6625-01-492-9713, test program set

Section Quantity:

1

Capacitance Value Per Section:

100.000 microfarads single section

Nonderated Operating Temp:

85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

10.0 microamperes

Tolerance Range Per Section:

-10.00/+10.00 microfarads single section

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

8.000

Equivalent Series Resistance At Reference Temperature In Ohms:

0.80

Dc Leakage At Reference Temp:

10.000 microamperes

Reference Temperature At Which Rated:

85.0 degrees celsius

Terminal Surface Treatment:

Solder

Product Name:

Dipped radial tantalum capacitor

Special Features:

Voltage rating: 16 volts.

Test Data Document:

96906-mil-std-202 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

2 standoff, wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0