

View Online at <https://aerobasegroup.com/nsn/5910-01-532-9091>

**Body Style:**

W/o mtg facilities, radial terminals

**Terminal Length:**

0.187 inches

**Body Diameter:**

0.350 inches

**Body Length:**

0.710 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.200 inches

**Terminal Diameter:**

0.020 inches

**Electrical Polarization:**

Polarized

**End Application:**

6625-01-492-9713, test program set

**Section Quantity:**

1

**Capacitance Value Per Section:**

100.000 microfarads single section

**Nonderated Operating Temp:**

85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

10.0 microamperes

**Tolerance Range Per Section:**

-10.00/+10.00 microfarads single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

8.000

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.80

**Dc Leakage At Reference Temp:**

10.000 microamperes

**Reference Temperature At Which Rated:**

85.0 degrees celsius

**Terminal Surface Treatment:**

Solder

**Product Name:**

Dipped radial tantalum capacitor

**Special Features:**

Voltage rating: 16 volts.

**Test Data Document:**

96906-mil-std-202 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

2 standoff, wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0