Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-534-2774

· · · ·
Body Style:
Chip type
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.000
Body Length:
3.5 millimeters
Body Width:
2.8 millimeters
Body Height:
1.9 millimeters
End Application:
Training facility, visual flight simulation
Capacitance Value Per Section:
336.000 picofarads all sections
New density of One and the eliteration
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 ac/dc all sections
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 ac/dc all sections Tolerance Range Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 ac/dc all sections Tolerance Range Per Section: -10.00/+10.00 percent all sections
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 ac/dc all sections Tolerance Range Per Section: -10.00/+10.00 percent all sections Product Name:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 ac/dc all sections Tolerance Range Per Section: -10.00/+10.00 percent all sections Product Name: Standard tantalum
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 ac/dc all sections Tolerance Range Per Section: -10.00/+10.00 percent all sections Product Name: Standard tantalum Shelf Life:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 ac/dc all sections Tolerance Range Per Section: -10.00/+10.00 percent all sections Product Name: Standard tantalum Shelf Life: N/a
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 ac/dc all sections Tolerance Range Per Section: -10.00/+10.00 percent all sections Product Name: Standard tantalum Shelf Life: N/a
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 ac/dc all sections Tolerance Range Per Section: -10.00/+10.00 percent all sections Product Name: Standard tantalum Shelf Life: N/a Unit Of Measure:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 ac/dc all sections Tolerance Range Per Section: -10.00/+10.00 percent all sections Product Name: Standard tantalum Shelf Life: N/a Unit Of Measure: Demilitarization:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 ac/dc all sections Tolerance Range Per Section: -10.00/+10.00 percent all sections Product Name: Standard tantalum Shelf Life: N/a Unit Of Measure: Demilitarization: No