

View Online at https://aerobasegroup.com/nsn/5910-01-539-5975

Body Style:
Chip type
Reliability Indicator:
Not established
Body Length:
0.079 inches
Body Width:
0.049 inches
Body Height:
0.049 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
F-15 support equipment
Capacitance Value Per Section:
8.200 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Terminal Type And Quantity:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Terminal Type And Quantity: 2 bonding pad
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure:  Demilitarization: No