

View Online at https://aerobasegroup.com/nsn/5910-01-549-0309

Body Style: Chip type Reliability Indicator: Not established Body Length: 0.008 inches Body Width: 0.006 inches Body Height: 0.0067 inches Schematic Diagram Designator: No common or grounded electrode (s) End Application: C-17a aircraft Capacitance Value Per Section: 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius S0.0 dc single section 50.0 dc single section 10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Pemilitarization: No	
Reliability Indicator: Not established Body Length: 0.008 inches Body Width: 0.006 inches Body Height: 0.067 inches Schematic Diagram Designator: No common or grounded electrode (s) End Application: C-17a aircraft Capacitance Value Per Section: 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius S0.0 dc single section Tolerance Range Per Section: 10.00/+10.00 picofarads single section Toley Hough Per Section: 10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Style:
Not establishedBody Length:0.008 inchesBody Width:0.006 inchesBody Height:0.067 inchesSchematic Diagram Designator:No common or grounded electrode (s)End Application:C-17a aircraftCapacitance Value Per Section:0.150 microfarads single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 125.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:50.0 dc single sectionTolerance Range Per Section:-10.00/+10.00 picofarads single sectionTerminal Type And Quantity:2 bonding padShelf Life:N/aUnit Of Measure:Demilitarization:No	Chip type
Body Length: 0.008 inches Body Width: 0.006 inches Body Height: 0.067 inches Schematic Diagram Designator: No common or grounded electrode (s) End Application: C-17a aircraft Capacitance Value Per Section: 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Reliability Indicator:
0.008 inches Body Width: 0.006 inches Body Height: 0.067 inches Schematic Diagram Designator: No common or grounded electrode (s) End Application: C-17a aircraft Capacitance Value Per Section: 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Folerance Range Per Section: 1.0.00/+10.00 picofarads single section Capadia Single section Capadia Single Section Carminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Not established
Body Width: 0.006 inches Body Height: 0.067 inches Schematic Diagram Designator: No common or grounded electrode (s) End Application: C-17a aircraft Capacitance Value Per Section: 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Length:
0.006 inches Body Height: 0.067 inches Schematic Diagram Designator: No common or grounded electrode (s) End Application: C-17a aircraft Capacitance Value Per Section: 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Monderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	0.008 inches
Body Height: 0.067 inches Schematic Diagram Designator: No common or grounded electrode (s) End Application: C-17a aircraft Capacitance Value Per Section: 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Width:
0.067 inches Schematic Diagram Designator: No common or grounded electrode (s) End Application: C-17a aircraft Capacitance Value Per Section: 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Monderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.006 inches
Schematic Diagram Designator: No common or grounded electrode (s) End Application: C-17a aircraft Capacitance Value Per Section: 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Height:
No common or grounded electrode (s) End Application: C-17a aircraft Capacitance Value Per Section: 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.067 inches
End Application: C-17a aircraft Capacitance Value Per Section: 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Schematic Diagram Designator:
C-17a aircraft Capacitance Value Per Section: 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	No common or grounded electrode (s)
Capacitance Value Per Section: 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	End Application:
 0.150 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No 	C-17a aircraft
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization:	Capacitance Value Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.150 microfarads single section
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Nonderated Operating Temp:
50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between -55.0 degrees celsius and 125.0 degrees celsius
Tolerance Range Per Section: -10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Nonderated Continuous Voltage Rating And Type Per Section:
-10.00/+10.00 picofarads single section Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	50.0 dc single section
Terminal Type And Quantity: 2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	Tolerance Range Per Section:
2 bonding pad Shelf Life: N/a Unit Of Measure: Demilitarization: No	-10.00/+10.00 picofarads single section
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No	2 bonding pad
Unit Of Measure: Demilitarization: No	Shelf Life:
 Demilitarization: No	N/a
No	Unit Of Measure:
No	
	Demilitarization:
	No
Filg:	Fiig:
A010b0	A010b0