NSN 5910-01-550-8339

Fiig: A010b0

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-550-8339

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.100
Terminal Length:
Between 1.500 inches and 2.250 inches
Body Diameter:
0.750 inches
Body Length:
2.125 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.03 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
270.0 ac-rms single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Case Insulation Material:
Plastic
Test Data Document:
81349-mil-prf-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 uninsulated wire lead
Specification Data:
81349-mil-prf-39022/12 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

NSN 5910-01-550-8339

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-39022 spec.