

View Online at https://aerobasegroup.com/nsn/5910-01-558-8357

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.1000

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.607 inches

**Body Length:** 

1.531 inches

**Terminal Diameter:** 

0.032 inches

End Application:

Ac-130u

Capacitance Value Per Section:

2.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Range Per Section:** 

-5.00/+5.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

100000.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

0.3000

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

## **Test Data Document:**

81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a



Demilitarization:

No

Fiig:

A010b0