Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-564-4903

## **Body Style:**

W/o mtg facilities, radial terminals

# **Reliability Indicator:**

Not established

# **Terminal Length:**

Between 0.155 inches and 0.219 inches

## **Body Diameter:**

0.250 inches

## **Body Length:**

0.400 inches

# Center To Center Distance Between Terminals Parallel To Length:

0.200 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

## **Electrical Polarization:**

Polarized

## End Application:

Mark iii helicopters (sh-60b); panel id cass otps; cca, age (a1); mh-60 r/s cass otps: panel id pccn: p2j990

## **Capacitance Value Per Section:**

10.000 microfarads single section

# Nonderated Operating Temp:

85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

25.0 ac/dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### **Capacitive Electrode Material:**

Tantalum

### **Product Name:**

Inavy: capacitor; cage: tantalum dipped/radial-polar t356 series "ultradip" capacitor

# Terminal Type And Quantity:

2 uninsulated wire lead

### Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A010b0