## NSN 5910-01-569-2550

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-569-2550 **Body Style:** W/mtg bracket, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.1000 **Terminal Length:** 1.625 inches **Body Diameter:** 0.562 inches **Body Length:** 1.625 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Mounting Facility Type And Quantity:** 1 unthreaded mounting holes **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 0.390 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section Case Material: Metal **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polyethylene terephthalate **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5910-01-569-2550

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A010b0