NSN 5910-01-570-3059

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-570-3059

Body Style:
W/mtg hol (s)/slot(s), terminals on opposite surfaces
Reliability Indicator:
Not established
Body Length:
Between 2.625 inches and 3.375 inches
Body Width:
1.000 inches
Body Height:
0.500 inches
Terminal Diameter:
0.175 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
End Application:
Diode driver assembly (5999-01-569-9393)
Mounting Facility Type And Quantity:
1 unthreaded mounting holes
Capacitance Value Per Section:
820.000 microfarads single section
Nonderated Operating Temp:
Potugon EE 0 dogress coloius and 9E 0 dogress coloius
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section Tolerance Range Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material:
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Product Name:
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Product Name: Cage: type mlp 85 degrees c flatpack, ultra-long life, aluminum
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Product Name: Cage: type mlp 85 degrees c flatpack, ultra-long life, aluminum Terminal Type And Quantity:
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Product Name: Cage: type mlp 85 degrees c flatpack, ultra-long life, aluminum Terminal Type And Quantity: 2 wire hook/loop
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Product Name: Cage: type mlp 85 degrees c flatpack, ultra-long life, aluminum Terminal Type And Quantity: 2 wire hook/loop Shelf Life:
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Product Name: Cage: type mlp 85 degrees c flatpack, ultra-long life, aluminum Terminal Type And Quantity: 2 wire hook/loop Shelf Life: N/a
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Product Name: Cage: type mlp 85 degrees c flatpack, ultra-long life, aluminum Terminal Type And Quantity: 2 wire hook/loop Shelf Life: N/a
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Product Name: Cage: type mlp 85 degrees c flatpack, ultra-long life, aluminum Terminal Type And Quantity: 2 wire hook/loop Shelf Life: N/a Unit Of Measure:
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 ac/dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Metal Product Name: Cage: type mlp 85 degrees c flatpack, ultra-long life, aluminum Terminal Type And Quantity: 2 wire hook/loop Shelf Life: N/a Unit Of Measure: Demilitarization: