## NSN 5910-01-584-4884

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-584-4884

| Body Style:  |
|--|
| W/o mtg facilities, axial terminals                        |
| Reliability Indicator:                                     |
| Established  |
| Reliability Failure Rate Level In Percent:                 |
| 0.010  |
| Terminal Length:   |
| 1.625 inches   |
| Body Diameter:   |
| 0.235 inches   |
| Body Length:   |
| 0.813 inches   |
| Terminal Diameter:   |
| 0.025 inches   |
| Schematic Diagram Designator:                              |
| No common or grounded electrode (s)                        |
| End Application:   |
| Fighter aircraft (f19 e/f)                                 |
| Capacitance Value Per Section:                             |
| 0.015 microfarads single section                           |
| Nonderated Operating Temp:                                 |
| Between -65.0 degrees celsius and 125.0 degrees celsius    |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 400.0 dc single section                                    |
| Tolerance Range Per Section:                               |
| -0.50/+0.50 percent single section                         |
| Case Material:   |
| Metal  |
| Terminal Type And Quantity:                                |
| 2 uninsulated wire lead                                    |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A010b0   |